

An Intellectual Property Law Firm

Mark DiPietro

3200 IDS Center 80 South Eighth Street Minneapolis, Minnesora 55402-2215 USA TEL 612.332.5300 FAX 612.332.9081 www.merchantgould.com

A Professional Conversion.

Fax Transmission

May 9, 2003

TO:

Commissioner for Patents

Attn: Examiner Alicia Ann Chevalier

Patent Examining Corps

Facsimile Center

Total pages, including cover letter:

Washington, D.C. 20231

OUR REF:

FROM:

9340.680USI1

PTO FAX NUMBER 1-703.872.9310

If you do NOT receive all of the pages, please telephone us at 612.371.5375, or fax us at 612.332.9081.

Title of Document Transmitted:

Amendment and Response

Applicant:

Giuseppe Puppin

Serial No.:

09/522,353

Filed:

03/09/2000

Group Art Unit: 3094

Our Ref. No.:

9340.680USI1

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2725. Please consider this a PETITION FOR EXTENSION OF TIME for a sufficient number of months to enter these papers, if appropriate.

> Name: Mark DiPietro Reg. No.: 28,707

I hereby certify that this paper is being transmitted by facsimile to the U.S. Patent and Trademark Office on the date shown below.

Darlene M. Stack



S/N 09/522,353

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

PUPPIN

Examiner:

A. CHEVALIER

Serial No.:

09/522,353

Group Art Unit:

1772

Filed:

MARCH 9, 2000

Docket No.:

9340.680USI1

Title:

HINGED THERMOPLASTIC-FABRIC REINFORCED STRUCTURA

MEMBER, PROFILE AND METHODS THEREFORE

AMENDMENT AND RESPONSE

Mail Stop: Non-Fee Amendment Commissioner for Patents P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

In response to the Office Action dated February 11, 2003, Applicants submit the following Amendment and Remarks. Reconsideration of the claims is respectfully requested.

AMENDMENTS

In the Claims

Please amend the claims to read as follows:

1. (Thrice Amended) A hinged, composite structure comprising a first rigid thermoplastic area, a second rigid thermoplastic area, and at least one flexible hinged region, wherein a fabric is embedded in the first rigid thermoplastic composite area and the second rigid thermoplastic composite area and hinged region, and wherein said first and second rigid areas are joined through the at least one flexible hinged region, so as to permit rotation of the first rigid area relative to the second rigid area about the hinged region, wherein the first rigid area and the second rigid area include bends at predetermined distances from the hinged region, and wherein further at least one portion of said at least one flexible hinged region is coated with a flexible scalant.